



## Wall Pack Lights



### Excellent Heat Dissipation

The specially designed heat sink does not let dust easily collect, while also allowing more air to flow through it, providing for greater heat dissipation and, in turn, improving the performance of a long-lasting, durable luminaire.



### Anti-Corrosion Function

By adopting dedicated processing treatment on heat sink and other parts, the luminaire has excellent anti-corrosive and UV-resistant function.



### Robust, Protective Design

A robust, protective design gives this luminaire a high IP rating and the ability to handle harsh environments.



### Optimal Optical Design

The unique and scientific combination design of lens and diffuser used gives good quality and quantity of light, where you need it. With options of beam angles to choose from, these luminaires are ideal for a number of applications.



### Quality Core Component

Excellent luminaire design to the core: starting with the LED packages themselves. These luminaires only use high quality LEDs – chipsets that have great quality and long life as backed by LM-80 and TM-21 reports. Quality inside the luminaires that shines from the outside.

## SERIES

### Wall Pack Family

Together, these wall packs form a family of products, thereby offering a suite of luminaires suitable for a variety of indoor and outdoor applications.



Yost Inc.

# Wall Pack Lights



WP-5100

### Specifications

Material: Aluminum/Glass  
 Housing Color: Bronze  
 Driver: Built-in  
 Input Voltage: 90-305V or 180V-528V  
 Power Factor:  $\geq 0.9$   
 Operating Temperature:  $-25^{\circ}\text{C}$ – $+45^{\circ}\text{C}$ ,  $-13^{\circ}\text{F}$ – $+113^{\circ}\text{F}$   
 IP Rating – 65  
 Lifetime – 50,000 Hours



CE RoHS DLC




WP-5150



Model No.	Power (W)	Luminous Flux (lm)	Luminous Efficacy (lm/W)	Color Temp. (K)	CRI (Ra)	Beam Angle ( $^{\circ}$ )	Dimensions W x D x H (inches)	Weight (kg/lb)
WP-5060-113	60	5400	90	3000	$\geq 75$	110x130	14.3 x 7.6 x 9.0	3.6/8.0
WP-5060-112	60	5400	90	4000	$\geq 75$	110x130	14.3 x 7.6 x 9.0	3.6/8.0
WP-5060-111	60	5400	90	5000	$\geq 75$	110x130	14.3 x 7.6 x 9.0	3.6/8.0
WP-5080-113	80	7200	90	3000	$\geq 75$	110x130	14.3 x 7.6 x 9.0	3.6/8.0
WP-5080-112	80	7200	90	4000	$\geq 75$	110x130	14.3 x 7.6 x 9.0	3.6/8.0
WP-5080-111	80	7200	90	5000	$\geq 75$	110x130	14.3 x 7.6 x 9.0	3.6/8.0
WP-5100-113	100	9500	95	3000	$\geq 75$	110x130	14.3 x 7.6 x 9.0	3.6/8.0
WP-5100-112	100	9500	95	4000	$\geq 75$	110x130	14.3 x 7.6 x 9.0	3.6/8.0
WP-5100-111	100	9500	95	5000	$\geq 75$	110x130	14.3 x 7.6 x 9.0	3.6/8.0
WP-5150-111	150	13500	90	5000	$\geq 75$	110x130	14.3 x 7.6 x 9.0	3.6/8.0

#### Color Temperature



#### Lighting Distribution Type IV

